

AMENDMENTS TO THE SPECIFICATION

Please replace the paragraph beginning at page 12, line 8, with the following rewritten paragraph:

[0027] The spray nozzle unit 10 is removably attached to the tip end of a swing arm 34. In this embodiment, the spray nozzle unit 10 is composed of one or a plurality of (for example, two) spray nozzles 10a, and a nozzle support member 10b supporting the ~~spry~~ spray nozzle 10a. Each spray nozzle 10a is removably attached to the nozzle support member 10b with a support metal fitting, and the position of the nozzle support member 10b can be adjusted in a longitudinal direction and around a center by adjusting the support metal fitting. Furthermore, in this embodiment, the nozzle support member 10b is attached to the swing arm 34 via a cleaning solution pipe 35. To be more specific, the nozzle support member 10b is removably attached to the cleaning solution pipe 35 with, for example, a screw fixture 10c, and the cleaning solution pipe 35 is removably attached to the swing arm 34, for example, with a screw fixture 35a and a Ferrule clamp 35b. However, the spray nozzle unit 10 as well as the nozzle support member 10b are not limited to such configurations, and may be directly attached removably to the tip end of the swing arm 34. The cleaning solution pipe 35 is supplied with a cleaning solution via a cleaning solution tube (not shown). Then, the cleaning solution is ejected from a cleaning nozzle 35c connected to the cleaning solution pipe 35 to the inside of the rotary drum 2, whereby the inside of the rotary drum 2 is cleaned.